# LED MEMO4



# INDOOR SIGN LUMINARIES

# APPLICATION AREA:

Self testing emergency sign luminary with LEDs for use to the indoor spaces of the vessel.

## **DESIGN:**

According to the rules of international classification societes, VDE and IEC.

## **HOUSING:**

Aluminum.

Diffuser made of clear plexiglass.

## LAMPS:

## LED Module.

## MOUNTING:

Wall or ceiling installation. Flush mounted base available.

## **ELECTRIC:**

230V 50 or 60Hz,

Flexible cable, heat resistant up to 105°C.

#### PROTECTION:

IP40.



290

38

60

92





152

## **ORDER CODES:**

OPERATION VOLTAGE	220-240V AC/ 50-60Hz
MAXIMUM POWER CONSUMPTION	3,8W/6,7VA
BATTERY (Ni-Cd)	3,6V/ 1,5Ah
BATTERY PROTECTION	From overcharge and full discharge
INDICATION - CONTROLS	Charge, Indication LED, Test button
CHARGING TIME	24H
MINIMUM AUTONOMOUS DURATION	180 min
ILIUMINATION SOURCE	15 white LEDs
ILIUMINATION ( 230V/EMERGENCY)	125/125 lm
DEGREES OF COVER PROTECTION	IP40