MOFS06



STAINLESS STEEL FLOODLIGHT FOR HST/HSI E40 LAMP



APPLICATION AREA:

Multipurpose floodlights for engine rooms, weather-exposed areas, cargo holds, decks, stores, workshops, industrial areas.

DESIGN:

According to the rules of international classification societes, VDE and IEC.

HOUSING:

Stainless steel, powder coated white RAL 9016.

Diffuser made of safety glass.
Reflector made of anodized aluminum, wide beam angle.

MOUNTING:

Stainless steel bracket with three holes ř17.

CONNECTION:

Junction box with 6mm, terminal and ignitors

ELECTRIC:

230 V 50 or 60 Hz. Flexible cable, heat resistant.

LAMPS:

HST/HSI-E40.

CABLE ENTRY:

Brass cable gland M25.

450

ORDER CODES:

CODE	VOLTAGE	FREQUENCY	POWER	LAMP
MOFS6-2E40	PLEASE SEE THE BALLAST UNIT TABLE			E40

BALAST UNIT FOR HST/HSI E40 LAMPS:

CODE	VOLTAGE	FREQUENCY	WEIGHT
MOFS6 BU-1000-11	230V	50Hz	19 Kg
MOFS6 BU-1000-12	230V	60Hz	19 Kg

